

What is claimed is:

1 1. A method for optimizing a solution set for a problem
2 comprising the sequential steps of:

3 a) generating a first set of solutions comprising a plurality of
4 members;

5 b) creating a second set of solutions using a selection
6 operator to select members from said first set of solutions;

7 c) creating a probabilistic model fitting said second set of
8 solutions, said probabilistic model allowing for multiple variables to be merged
9 together to form a single new variable whereby hierarchically decomposable
10 problems can be modeled;

11 d) using said model to generate a third set of solutions; and,

12 e) replacing at least a portion of said first set of solutions
13 with said third set of solutions to create a new solution set.

1 2. A method for optimizing a solution set as in claim 1
2 wherein the step of creating a model fitting said second set of solutions
3 comprises creating a plurality of models that fit said second set of solutions,
4 selecting one model from said plurality of models, and using said one model to
5 create said third set of solutions.

6
7
8 3. A method for optimizing a solution set as in claim 2
9 wherein the step of selecting one model comprises using a scoring metric to
10 score each of said models and searching said scored models to determine the
11 highest scoring of said plurality of models.

12
13 4. A method for optimizing a solution set as in claim 3
14 wherein said scoring metric is chosen from the group of scoring metrics
15 consisting of a minimum description length metric, and the Bayesian-Dirichlet

metric; and wherein the step of searching all of said scored networks comprises using a search method chosen from the group consisting of a greedy algorithm method, a local hill climbing method, a gradient search, a tabu search, and a simulated annealing method.

5. A method for optimizing a solution set as in claim 2 wherein the step of selecting one model comprises comparing said plurality of models through a binary relation to define a better than relation between said models.

6. A method for optimizing a solution set as in claim 1 wherein the step of creating a probabilistic model comprises creating a model that models dependencies, independencies, conditional dependencies, and conditional independencies on a plurality of hierarchical levels between at least a portion of said merged variables.

7. A method for optimizing a solution set as in claim 1 wherein the step of creating a probabilistic model fitting said second set of solutions comprises creating one or more models chosen from the group consisting of Bayesian networks with local structures, and Huffman networks.

8. A method for optimizing a solution set as in claim 1 wherein the step of creating a probabilistic model comprises creating a probabilistic model that utilizes local structures to represent conditional probabilities between variables.

9. A method for optimizing a solution set as in claim 1 wherein the step of creating a model fitting said second set of solutions comprises creating a Bayesian network model comprising one or more features to model a hierarchal problem decomposition, said one or more features

selected from the group consisting of local structures, hidden variables, and histograms.

10. A method for optimizing a solution set as in claim 1 wherein the step of creating a model fitting said second set of solutions comprises creating a Bayesian network model comprising local structures selected from the group consisting of default tables, decision trees, and decision graphs.

11. A method for optimizing a solution set as in claim 1 wherein the step of creating a probabilistic model comprises building a network to model a probability distribution of said second set of solutions, said network representing a plurality of merged variables as a single variable, said network representing dependencies and independencies between at least a portion of said merged variables over a plurality of hierarchical levels.

12. A method as in claim 11 wherein the step of building said network comprises building said network using a scoring metric and a search method to optimize said network.

13. A method for optimizing a solution set as in claim 1 wherein the step of generating a probabilistic model fitting said second set of solutions comprises generating a plurality of probabilistic models fitting said second set of solutions, each of said models allowing for multiple variables to be merged together to form a single new variable whereby hierarchically decomposable problems can be modeled; and wherein the step of using said probabilistic model to generate a third set of solutions comprises using each of said plurality of models to generate a portion of said third set of solutions.

14. A method for optimizing a solution set as in claim 13, wherein the method further comprises the step of using a first of said plurality

1 of models to generate a selected percentage of said third set of solutions, and
2 using a second of said plurality of solutions to generate a selected percentage of
3 said third set of solutions.

4
5 15. A method for optimizing a solution set as in claim 1
6 wherein the method further comprises a step of performing niching to preserve
7 diversity of solutions.

8
9 16. A method for optimizing a solution set as in claim 1
10 wherein said selection operator provides for niching to preserve diversity
11 among said members of said second set.

12
13 17. A method for optimizing a solution set as in claim 1
14 wherein said selection operator comprises a restricted tournament selection
15 operator.

16
17 18. A method for optimizing a solution set as in claim 1
18 wherein said selection operator comprises one or more operators selected from
19 the group consisting of a tournament selection operator, a truncation selection
20 operator, a fitness selection operator, a preselection operator, a crowding
21 selection operator, a clustering selection operator, a lambda-mu selection
22 operator, and a Boltzmann selection operator.

23
24 19. A method for optimizing a solution set as in claim 1
25 wherein the step of replacing at least a portion of said first solution set with
26 said third solution set further comprises replacing at least a portion of said first
27 solution set with said third solution set using a replacement operator that
28 provides for niching.

29
30 20. A method for optimizing a solution set as in claim 19
31 wherein said replacement operator performs niching using a niching method

selected from the group of methods consisting of tournament replacement and crowding.

21. A method for optimizing a solution set as in claim 20 wherein said replacement operator comprises restricted tournament replacement.

22. A method for optimizing a solution set as in claim 1 wherein the step of replacing at least a portion of said first set of solutions comprises performing niching to preserve diversity of said solutions through the steps of:

subdividing said first set of solutions into a plurality of sub-sets;
comparing one of said third set of solutions with members of one of said sub-sets; and
replacing one of said members of said sub-sets with said one of said third set of solutions if said one of said third solution set is superior to said members of said one of said sub-sets.

23. A method for optimizing a solution set as in claim 22 wherein each of said sub-sets have between 15-25 members.

24. A method for optimizing a solution set as in claim 22 wherein each of said sub-sets have a number of members greater than 25 and proportional to the size of the problem being solved.

25. A method for optimizing a solution set as in claim 1 wherein the step of creating a second set of solutions from said first set of solutions comprises creating a plurality of second sets of solutions, wherein the step of creating a probabilistic model fitting said second set comprises creating a probabilistic model fitting each of said second sets, wherein the step of using said model to generate a third set of solutions comprises using each of said

1 probabilistic models to generate a plurality of third sets of solutions, and
2 wherein the step of replacing at least a portion of said first set of solutions with
3 said third set comprises replacing at least a portion of said first set with each of
4 said third sets of solutions.

5
6 26. A method for optimizing a solution set as in claim 1
7 wherein the method further comprises a step of:

8 evaluating said new solution set to determine if completion
9 criteria are satisfied, and if said completion criteria are not satisfied replacing
10 said first set of solutions with said new set of solutions and repeating the steps
11 of b) through e) until said completion criteria are satisfied.

12
13 27. A method for optimizing a solution set as in claim 1
14 wherein the step of using a selection operator to create a second set of
15 members from said first set further comprises using a fitness function to
16 determine a fitness for each of said members, and wherein said selection
17 operator selects members having a high fitness.

18
19 28. A method for optimizing a solution set as in claim 27
20 wherein said fitness function comprises one or more fitness functions selected
21 from the group consisting of a co-evolved fitness function, a multi-objective
22 fitness function, a multi-modal fitness function, an interactive fitness function,
23 an approximate fitness function, a simulation fitness function, and an execution
24 fitness function.

25
26 29. A method for optimizing a solution set as in claim 1
27 wherein the step of generating a first set of solutions comprises generating said
28 first set of solutions using a probability distribution biased by prior knowledge.

1 30. A method for optimizing a solution set as in claim 1
2 wherein said members of said first solution set are coded in a format selected
3 from the group consisting of fixed and variable length strings.

4
5 31. A method for optimizing a solution set as in claim 30
6 wherein said members of said first solution set are in a format that comprises
7 one or more formats selected from the group consisting of: binary code, k-ary
8 code, floating point code, alphanumeric code, real vectors, logical expressions,
9 program codes, images, random keys, and rules.

10
11 32. A method for optimizing a solution set as in claim 1
12 wherein the method further comprises the preliminary step of converting data
13 into said first solution set.

14
15 33. A method for optimizing a solution set for a problem
16 comprising the steps of:

17 generating a first set of solutions comprising a plurality of
18 members;

19 creating a second set of solutions by selecting a sub-set of
20 members from said first set of solutions;

21 creating a probabilistic model fitting said second set of solutions;

22 using said model to generate a third set of solutions; and,

23 replacing at least a portion of said first set of solutions with said
24 third set of solutions to create a new solution set, said replacing comprising
25 niching to preserve diversity among members of said new solution set.

26
27 34. A method for optimizing a solution set as in claim 33
28 wherein the step of replacing at least a portion of said first set of solutions with
29 said third set with niching is performed using one or more operators chosen
30 from the group consisting of a tournament operator, a crowding operator, a pre-
31 selection operator, a clustering operator, and a fitness sharing operator.

1
2 35. A method for optimizing a solution set as in claim 33
3 wherein the step of replacing at least a portion of said first set of solutions with
4 niching comprises the steps of:

5 subdividing said first set of solutions into a plurality of sub-sets;
6 comparing one of said third set of solutions with members of one
7 of said sub-sets; and

8 replacing one of said members of said sub-sets with said one of
9 said third set of solutions if said one of said third solution set is superior to said
10 members of said one of said sub-sets.

11
12 36. A method for optimizing a solution set as in claim 33
13 wherein each of said sub-sets have between 15-25 members.

14
15 37. A method for optimizing a solution set as in claim 33
16 wherein the step of creating a second set of solutions comprises using a
17 selection operator to select members from said first solution set, said selection
18 operator comprises one or more operators chosen from the group consisting of
19 a tournament selection operator, a crowding operator, a pre-selection operator,
20 a clustering operator, and a fitness sharing operator.

21
22 38. A method for optimizing a solution set for a problem
23 comprising the sequential steps of:

24 a) generating a first set of solutions comprising a plurality of
25 members;

26 b) creating a second set of solutions using a selection
27 operator to select a second set of members from said first set of solutions, said
28 selection operator using a fitness function to evaluate said members of said first
29 set, said second set members having a high fitness;

30 c) building a network to model a probability distribution of
31 said second set of solutions, said network representing a plurality of merged

variables as a single variable, said network representing dependencies and independencies between at least two of said merged variables over a plurality of hierarchical levels;

d) using said model to generate a third set of solutions;

e) replacing at least a portion of said first set of solutions with said third set of solutions to create a new solution set, said replacing comprising niching to preserve diversity among members of said new solution set; and

f) evaluating said new solution set to determine if completion criteria have been satisfied, and if said completion criteria are not satisfied replacing said first set of solutions with said new set of solutions and repeating the steps of b) through e) until said completion criteria are satisfied.

39. A computer program product for optimizing a solution set, the program product comprising computer executable instructions stored on a computer readable medium that when executed by a computer cause the computer to:

a) create a second set of solutions using a selection operator to select members from a first set of solutions;

b) build a probabilistic model fitting said second set of solutions, said probabilistic model allowing for multiple variables to be merged together to form a single new variable, and said model allowing for relationships to be modeled between at least a portion of said single new variables over a plurality of hierarchical levels;

c) using said model to generate a third set of solutions;

d) replacing at least a portion of said first set of solutions with said third set of solutions to create a new solution set; and,

e) evaluating said third set of solutions to determine if completion criteria have been satisfied.

1 40. A computer program product as in claim 39, wherein the
2 program instructions when executed to cause the computer to build said
3 probabilistic model cause the computer to build a Bayesian network that
4 comprises local structures to model dependencies and independencies between
5 at least a portion of said merged variables.
6

7 41. A computer program product as in claim 39 wherein the
8 program instructions when executed further cause the computer to
9 communicate with at least a second computer, and to cause the at least a second
10 computer to execute one or more of the program product instructions.
11

12 42. A computer program product as in claim 41 wherein the
13 program instructions when executed cause the computer to communicate at
14 least a portion of said first set of solutions to the second computer for
15 processing by the second computer.
16

17 43. A computer program product as in claim 39 wherein the
18 program instructions when executed cause the computer to communicate with
19 the second computer to communicate instructions to the second computer for
20 building at least a portion of said probabilistic model.
21

22 44. A computer program product as in claim 39 wherein the
23 program instructions when executed further cause the computer to replace at
24 least a portion of said first set of solutions with said third set of solutions using
25 a niching method to preserve diversity of solutions in said new solution set.
26

27 45. A computer program product for optimizing a solution set,
28 the program product comprising computer executable instructions stored on a
29 computer readable medium that when executed by a computer cause the
30 computer to:

1 a) create a second set of solutions using a selection operator
2 that selects members from a first set of solutions;
3 b) build a probabilistic model that fits said second set of
4 solutions;
5 c) use said model to generate a third set of solutions;
6 d) replace at least a portion of said first set of solutions with
7 said third set of solutions to create a new solution set using niching to preserve
8 diversity among said new solution set;
9 e) evaluate said third set of solutions to determine if
10 completion criteria have been satisfied, and if said completion criteria have not
11 been satisfied to replace said first set of solutions with said new set and to
12 repeat steps a)-e).

13
14 46. A computer program product as in claim 45 wherein the
15 program instructions when executed cause the computer to replace at least a
16 portion of said first set of solutions with niching further causes the computer to:
17 subdivide said first set of solutions into a plurality of sub-sets;
18 compare one of said third set of solutions with members of one of
19 said sub-sets; and
20 replace one of said members of said sub-sets with said one of said
21 third set of solutions if said one of said third solution set is superior to said
22 members of said one of said sub-sets.